

HP 620/50/B12 P28

Spannung: 45 V

nl=3120.0U/min
ns=71.5U/min/VIo=4.7A
kn=-21.38U/min/A

kM=17.89Ncm/A

Spannung [V]	Strom [A]	Drehzahl [U/min]	Pin [W]	Pout [W]	Drehmoment [Ncm]	Wirkungsgrad [%]
44.9	10.0	3032.6	449.1	301.1	94.8	67.06
44.9	11.0	3006.5	493.9	354.9	112.7	71.84
44.9	12.0	2980.6	538.8	407.6	130.6	75.66
44.9	13.0	2954.9	583.7	459.5	148.5	78.73
44.9	14.0	2929.5	628.5	510.4	166.4	81.21
44.9	15.0	2904.4	673.4	560.5	184.3	83.23
44.9	16.0	2879.5	718.2	609.6	202.2	84.88
44.9	17.0	2854.8	763.0	657.9	220.1	86.22
44.9	18.0	2830.4	807.9	705.3	237.9	87.30
44.9	19.0	2806.2	852.7	751.8	255.8	88.17
44.9	20.0	2782.3	897.5	797.5	273.7	88.86
44.9	21.0	2758.6	942.3	842.4	291.6	89.40
44.9	22.0	2735.1	987.1	886.5	309.5	89.80
44.9	23.0	2711.9	1031.9	929.8	327.4	90.10
44.9	24.0	2689.0	1076.7	972.3	345.3	90.30
44.9	25.0	2666.3	1121.5	1014.0	363.2	90.42
44.9	26.0	2643.8	1166.3	1055.0	381.1	90.46
44.9	27.0	2621.6	1211.1	1095.3	399.0	90.44
44.9	28.0	2599.6	1255.9	1134.8	416.8	90.36
44.8	29.0	2577.9	1300.6	1173.6	434.7	90.23
44.8	30.0	2556.4	1345.4	1211.7	452.6	90.07
44.8	31.0	2535.2	1390.1	1249.2	470.5	89.86
44.8	32.0	2514.2	1434.9	1285.9	488.4	89.62
44.8	33.0	2493.4	1479.6	1322.0	506.3	89.35
44.8	34.0	2472.9	1524.4	1357.5	524.2	89.05
44.8	35.0	2452.7	1569.1	1392.3	542.1	88.73
44.8	36.0	2432.7	1613.8	1426.5	560.0	88.39
44.8	37.0	2412.9	1658.5	1460.1	577.9	88.04
44.8	38.0	2393.4	1703.3	1493.2	595.8	87.67
44.8	39.0	2374.1	1748.0	1525.6	613.6	87.28
44.8	40.0	2355.1	1792.7	1557.5	631.5	86.88
44.8	41.0	2336.3	1837.4	1588.9	649.4	86.48
44.8	42.0	2317.8	1882.0	1619.7	667.3	86.06
44.8	43.0	2299.5	1926.7	1650.0	685.2	85.64
44.8	44.0	2281.4	1971.4	1679.8	703.1	85.21
44.8	45.0	2263.6	2016.1	1709.1	721.0	84.77
44.8	46.0	2246.0	2060.7	1737.9	738.9	84.33
44.8	47.0	2228.7	2105.4	1766.2	756.8	83.89
44.8	48.0	2211.7	2150.1	1794.1	774.7	83.45
44.8	49.0	2194.8	2194.7	1821.6	792.5	83.00
44.8	50.0	2178.2	2239.3	1848.7	810.4	82.55