

HP 620/50/B12 P28

Spannung: 40 V

nl=2759.8U/min
ns=71.4U/min/V

Io=4.7A
kn=-19.13U/min/A

kM=18.07Ncm/A

Spannung [V]	Strom [A]	Drehzahl [U/min]	Pin [W]	Pout [W]	Drehmoment [Ncm]	Wirkungsgrad [%]
39.9	10.0	2684.4	399.0	271.7	96.6	68.08
39.9	11.0	2661.2	438.9	319.7	114.7	72.83
39.9	12.0	2638.2	478.8	366.8	132.8	76.61
39.9	13.0	2615.4	518.7	413.1	150.8	79.65
39.9	14.0	2592.8	558.5	458.6	168.9	82.11
39.9	15.0	2570.4	598.4	503.3	187.0	84.11
39.9	16.0	2548.3	638.3	547.2	205.0	85.73
39.9	17.0	2526.3	678.1	590.3	223.1	87.04
39.9	18.0	2504.6	718.0	632.6	241.2	88.10
39.9	19.0	2483.1	757.8	674.1	259.2	88.95
39.9	20.0	2461.7	797.7	714.9	277.3	89.62
39.9	21.0	2440.6	837.5	754.9	295.4	90.14
39.9	22.0	2419.7	877.4	794.3	313.4	90.53
39.9	23.0	2399.0	917.2	832.9	331.5	90.80
39.9	24.0	2378.6	957.0	870.8	349.6	90.98
39.9	25.0	2358.3	996.9	908.0	367.7	91.08
39.9	26.0	2338.2	1036.7	944.5	385.7	91.10
39.9	27.0	2318.4	1076.5	980.3	403.8	91.06
39.9	28.0	2298.8	1116.3	1015.5	421.9	90.97
39.9	29.0	2279.3	1156.2	1050.1	439.9	90.82
39.9	30.0	2260.1	1196.0	1084.0	458.0	90.63
39.9	31.0	2241.1	1235.8	1117.3	476.1	90.41
39.9	32.0	2222.3	1275.6	1149.9	494.1	90.15
39.9	33.0	2203.7	1315.4	1182.0	512.2	89.86
39.9	34.0	2185.4	1355.2	1213.5	530.3	89.55
39.9	35.0	2167.2	1395.0	1244.4	548.3	89.21
39.9	36.0	2149.2	1434.8	1274.8	566.4	88.85
39.9	37.0	2131.5	1474.5	1304.6	584.5	88.47
39.9	38.0	2114.0	1514.3	1333.8	602.5	88.08
39.8	39.0	2096.6	1554.1	1362.6	620.6	87.68
39.8	40.0	2079.5	1593.9	1390.8	638.7	87.26
39.8	41.0	2062.6	1633.6	1418.5	656.7	86.83
39.8	42.0	2045.9	1673.4	1445.8	674.8	86.40
39.8	43.0	2029.4	1713.2	1472.5	692.9	85.95
39.8	44.0	2013.2	1752.9	1498.8	710.9	85.50
39.8	45.0	1997.1	1792.7	1524.6	729.0	85.05
39.8	46.0	1981.3	1832.4	1550.0	747.1	84.59
39.8	47.0	1965.6	1872.2	1575.0	765.1	84.12
39.8	48.0	1950.2	1911.9	1599.5	783.2	83.66
39.8	49.0	1935.0	1951.7	1623.6	801.3	83.19
39.8	50.0	1920.0	1991.4	1647.4	819.3	82.72